#### DAKOTA MICRO, INC. LIMITED WARRANTY

Subject to the disclaims: limitations and other directions stated hereafter. Dakota Micro, in. warrants that the Product will be feen of dedects in anterial and workmanish for pariods as stated hereafter from the date of original purchase. THIS WARRANTY IS EXPRESSLY MADE IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUD-ING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS. THE EXCLUSINE REMEDY OF THE DUTRE IS LIMITED IN DESTRUCTION, INC. SHALL NOT DEL LIABLE FOR ANY LOSS, INCONVENIENCE, OR DAMAGE, INCLUDINS DIRECT, SPECIAL, INCI-DENTAL, OR CONSOCIUENTIAL DAMAGES, RESULTING FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER RESULTING FROM BREACH OF WARRANTY, NEGLI-CENCE, STRICT LIABILITY OF ANY OTHER LEGAL. THEORY, Any oral statements or representations made by anyone which are contrary to or at variance with the terms stated in this LIMITED WARRANTY are void.

Deloids Micro, Inc. (Hereinafter reflered to as "DM") will, at its option, either repair the defect or replace the defective Product or part thereof with a new or remanufactured equivalent at no charge to the purchaser for parts or labor for the period of three (3) years for AgCamEnduraCam monitors, quads and wireless, twelve Monitor (10) for all Over/feror camers at monitors as well as all other cables and accessories.

The DM limited warranty periods outlined above apply throughout the United States and Canada only. A one (1) year maximum limited warranty for all Products applies to all other

geographic locations unless otherwise stated in writing by DM.

This limited warranty does not apply to any issues connected with appearance that have no relation to the performance of the Product nor to any Product the extenior of which has been damaged or defaced, which has been subjected to improper voltage or other misuse, abnormal service or handling, or which has been altered or modified in design or construction.

In order to enforce the rights under this limited warranty, the purchaser should follow the process set forth on our website - www.dakotamicro.com, and provide proof of purchase to DM

Neither the sales personnel of DM nor any dealer or any other person is authorized to make any warranties other than those described herein, or to extend the duration of any warranties beyond the time periods described herein.

The warranties described herein shall be the sole and exclusive warranties and remedies provided by MD. Correction of defects, in the manner and for the period of time described herein, shall constitute compiled fulfillment of all liabilities and responsibilities of DM to the purchaser with respect to the Product and shall constitute full sastefaction of all diams. In no event shall DM be liable or in any way responsible for any damages or defects in the Product with vive were caused by receits or afferended rearies preferred by anymore other Hann DM.

Some states do not allow the limitation or evolusion of incidental or consequential damage, so said limitation may not apply to you. Ny endoon at law, suit in equity, or other judicial proceeding for the entirocement of any right provided for herein or otherwise, or, with respect to any claim that a purchaser may have against DM shall be instituted only in the Courts of the State of North Dakota, either in the state district out rotated in Whiteplon, North Dakota or in Federal District Court location in Fargo, North Dakota. Without regard to conflicts of law principles, the laws of the state of North Dakota shall gowern the interpretation and entirocement of the terms of this Limited Warranty and all aspects of the relationship between DM and the purchaser.

This warranty gives you specific legal rights and you may also have other rights, which may vary from state to state.

Rev: 06/04/20

# Included Analog Kit Components Dakota Micro, Inc.

www.dakotamicro.com



#### **CAMERA WARNINGS**

#### NEVER RELY ON YOUR AGCAM® /ENDURACAM® AS A SAFETY FEATURE.

It is up to your discretion to keep your road travel and other operations safe. Your AgCam<sup>9</sup>/EnduraCam<sup>9</sup> will provide you with information only based on what it sees. Operation of machinery safety quidelines still apply.

The AgCam® and EnduraCam® cameras are equipped with an array of infrared light emitters which are invisible to the human eye. This feature will aid in low light conditions but has limitations. The effective range of the night vision feature is 1 to 45+ feet and will produce a monochrome image only.

DO NOT ATTEMPT TO DRIVE MACHINERY USING THIS FEATURE.

## Camera Features

- Made in the USA, includes a 3 year warranty.
- Waterproof, shockproof, and suitable for nearly any use.
- 3-way programmable Video System (NTSC or PAL), Video output type (AHD or Analog) and Mirroring.
- Built-in, high quality CMOS camera with high performance infrared automatic (IR) illuminator modules.
- IR has effective range of 75ft+ in complete darkness.
- . To turn off the IR on the camera, remove the magnet from the
- plug labeled IR. Our exclusive Photogray camera body lens darkens in bright
- conditions and becomes completely transparent under low light conditions. This lens is also transparent of infrared light. allowing the LED's to penetrate even when it is darkened.
- . Optional lenses available include 46°, 21° and 15° Field of View (A complete lens guide is available on our website.)

### IMPORTANT INFORMATION REGARDING LEGACY ANALOG AND AHD EQUIPMENT

- · All Dakota Micro, Inc. monitors currently offered are AHD (Analog High Definition). Both CVBS (Legacy Analog) AgCam/EnduraCam cameras and AHD AgCam/EnduraCam cameras will
- function perfectly on the new Dakota Micro, Inc. AHD Monitors. Utilizing the AHD 9in or 7in monitors, customers can "mix and
- match" CVBS and AHD cameras · Be aware not all 3rd party monitors support AHD video.
- AHD Cameras WILL NOT work with Dakota Micro Analog wireless equipment

### Camera Specifications

Video System NTSC (Silver)/PAL (Black)

Video Type CVBS (Legacy Analog)

Sony 1/3in CMOS 16:9 Image Pick-up Device

Horizontal Resolution 480P (1200 TVL)

Minimum Illumination 0.01 LUX @ F1.2

Auto Electronic Shutter 1/50s~1/100.000s

Auto Gain Control High/Low Auto Switchable

Scanning System Progressive

Dynamic Range Digital Wide Dynamic Range

Standard Board Lens 92° FOV (Standard)

Custom Board Lens(s) Available 46°. 21°. 15° FOV

Photogray Triple Hardened Glass

Auto On/Off Back Light Compensation

Camera Body Lens

Waterproofing Criteria

Video Output CVBS (Analog)

Operating Temperature -45°F~150°F (-42°C~66°C)

Construction Aluminum Case

IP 69 Dimensions 2.13in (W) x 2.13in (L) x 2.12in (H)