

DAKOTA MICRO, INC. LIMITED WARRANTY

Subject to the disclaimer, limitations and other directions stated hereafter, Dakota Micro, Inc. warrants that the Product will be free from defects in material and workmanship for periods as stated hereafter from the date of original purchase. THIS WARRANTY IS EXPRESSLY MADE IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS. THE EXCLUSIVE REMEDY OF THE BUYER IS LIMITED TO REPAIR OR REPLACEMENT OF THE PRODUCT. EXCEPT AS STATED IN THIS WARRANTY, DAKOTA MICRO, INC. SHALL NOT BE LIABLE FOR ANY LOSS, INCONVENIENCE, OR DAMAGE, INCLUDING DIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, RESULTING FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER RESULTING FROM BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY OF ANY OTHER LEGAL THEORY. Any oral statements or representations made by anyone which are contrary to or at variance with the terms stated in this LIMITED WARRANTY are void.

Dakota Micro, Inc. (Hereinafter referred to as "DM") will, at its option, either repair the defect or replace the defective Product or part thereof with a new or remanufactured equivalent at no charge to the purchaser for parts or labor for the period of three (3) years for AgCam/EnduraCam cameras, two (2) years for AgCam/EnduraCam monitors, quads and wireless, twelve Months (12) for all OverView cameras & monitors as well as all other cables and accessories.

The DM limited warranty periods outlined above apply throughout the United States and Canada only. A one (1) year maximum limited warranty for all Products applies to all other geographic locations unless otherwise stated in writing by DM.

This limited warranty does not apply to any issues connected with appearance that have no relation to the performance of the Product nor to any Product the exterior of which has been damaged or defaced, which has been subjected to improper voltage or other misuse, abnormal service or handling, or which has been altered or modified in design or construction.

In order to enforce the rights under this limited warranty, the purchaser should follow the process set forth on our website - www.dakotamicro.com, and provide proof of purchase to DM.

Neither the sales personnel of DM nor any dealer or any other person is authorized to make any warranties other than those described herein, or to extend the duration of any warranties beyond the time periods described herein.


The warranties described herein shall be the sole and exclusive warranties and remedies provided by DM. Correction of defects, in the manner and for the period of time described herein, shall constitute complete fulfillment of all liabilities and responsibilities of DM to the purchaser with respect to the Product, and shall constitute full satisfaction of all claims. In no event shall DM be liable or in any way responsible for any damages or defects in the Product which were caused by repairs or attempted repairs performed by anyone other than DM.

Some states do not allow the limitation or exclusion of incidental or consequential damages, so said limitation may not apply to you. Any action at law, suit in equity, or other judicial proceeding for the enforcement of any right provided for herein or otherwise, or with respect to any claim that a purchaser may have against DM shall be instituted only in the Courts of the State of North Dakota, either in the state district court located in Wahpeton, North Dakota or in Federal District Court location in Fargo, North Dakota. Without regard to conflicts of law principles, the laws of the state of North Dakota shall govern the interpretation and enforcement of the terms of this Limited Warranty and all aspects of the relationship between DM and the purchaser. This warranty gives you specific legal rights and you may also have other rights, which may vary from state to state.

Rev: 10/19/21

Included Analog Kit Components

Dakota Micro, Inc.
www.dakotamicro.com



- 1 - Camera (Qty 1)
- 2 - 1/4-20 bolts (Qty 3)
- 3 - Camera Bracket (Qty 1)
- 4 - Mounting Magnet (Qty 1)
- 5 - 1/4-20 Nut (Qty 1)
- 6 - Nylon Washers (Qty 2)
- 7 - Camera Tail (Qty 1)
Not Pictured

CAMERA WARNINGS

NEVER RELY ON YOUR AGCAM® /ENDURACAM® AS A SAFETY FEATURE.

It is up to your discretion to keep your road travel and other operations safe. Your AgCam®/EnduraCam® will provide you with information only based on what it sees. Operation of machinery safety guidelines still apply.

The AgCam® and EnduraCam® cameras are equipped with an array of infrared light emitters which are invisible to the human eye. This feature will aid in low light conditions but has limitations. The effective range of the night vision feature is 1 to 45+ feet and will produce a monochrome image only.

DO NOT ATTEMPT TO DRIVE MACHINERY USING THIS FEATURE.

Camera Features

- Made in the USA, includes a 3 year warranty.
- Waterproof, shockproof, and suitable for nearly any use.
- 3-way programmable - Video System (NTSC or PAL), Video output type (AHD or Analog) and Mirroring.
- Built-in, high quality CMOS camera with high performance infrared automatic (IR) illuminator modules.
- IR has effective range of 75ft+ in complete darkness.
- Our exclusive Photogray camera body lens darkens in bright conditions and becomes completely transparent under low light conditions. This lens is also transparent of infrared light, allowing the LED's to penetrate even when it is darkened.
- Optional lenses available include 46°, 21° and 15° Field of View (A complete lens guide is available on our website.)

IMPORTANT INFORMATION REGARDING LEGACY ANALOG AND AHD EQUIPMENT

- All Dakota Micro, Inc. monitors currently offered are AHD (Analog High Definition). Both CVBS (Legacy Analog) AgCam/EnduraCam cameras and AHD AgCam/EnduraCam cameras will function perfectly on the new Dakota Micro, Inc. AHD Monitors.
- Utilizing the AHD 9in, 9in Quad or 7in monitors, customers can "mix and match" CVBS and AHD cameras.
- Be aware not all 3rd party monitors support AHD video.

Camera Specifications

Video System	NTSC (Silver)/PAL (Black)
Video Type	CVBS (Legacy Analog)
Image Pick-up Device	Sony 1/3in CMOS 16:9
Horizontal Resolution	480P (1200 TVL)
Minimum Illumination	0.01 LUX @ F1.2
Auto Electronic Shutter	1/50s~1/100,000s
Auto Gain Control	High/Low Auto Switchable
Scanning System	Progressive
Dynamic Range	Digital Wide Dynamic Range
Standard Board Lens	92° FOV (Standard)
Custom Board Lens(s)	Available 46°, 21°, 15° FOV
Camera Body Lens	Photogray Triple Hardened Glass
Back Light Compensation	Auto On/Off
Video Output	CVBS (Analog)
Operating Temperature	-45°F~150°F (-42°C~66°C)
Construction	Aluminum Case
Waterproofing Criteria	IP 69
Dimensions	2.13in (W) x 2.13in (L) x 2.12in (H)